




8 7 6 5 4 3 2 1



SECTION C-C B3-3



D4837-1 STRUT

RELEASED
2014-07-07
mo

- NOTES:**
- 1) MATERIAL: 17-4 PH/S17400/TYPE 630 SS ROUND BAR, H900 CONDITION
PER AMS 5643/ASTM A564
DART SPEC M17-4-R
 - 2) FINISH: N/A
 - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 - 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
 - 6) IDENTIFICATION: IDENTIFY PER QSI 044 6.6
 - 7) WEIGHT: 0.25 lbs
 - 8) LIQUID PENETRANT INSPECT PER QSI 038 6.1.1 (ASTM E1417 LEVEL 2)

APPROVED	DESIGN	RF	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
	DRAWN	RF		
	CHECKED	VS	DRAWING NO.	REV. C
	MFG. APPR.	JLM	D4837	SHEET 3 OF 3
	APPROVED	HS	TITLE	SCALE
	DE APPR.	DS	LEG ASSEMBLY	NTS
	DATE	14.06.24	<small>COPYRIGHT © 2013 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	

8 7 6 5 4 3 2 1